TACENS Gelus LITE II

- **NEW INTELLIGENT PWM 9CM 9dB ULTRA-SILENT AURA PRO FAN WITH EXCLUSIVE FLUXUS PRO BEARING AND ANTIVIBRATION SYSTEM**
- **POWERFUL THREE U-SHAPE COPPER SUPERCONDUCTOR HEATPIPES**
- **DIRECT HEATPIPE CPU CONTACT FOR FASTEST HEAT TRANSFER**
- **45 ALUMINIUM FINS**
- **LOW WEIGHT AND SMALL SIZE**
- **FAST AND EASY INSTALL. FOR LGA775/1366, AMD K8/AM2/AM3**

HEATSINK SPECIFICATIONS	
DIMENSIONS (mm)	82mm(L) x 50mm(W) x 112mm(H)
WEIGHT	320g
MATERIAL	COPPER SUPERCONDUCTOR HEATPIPES ALUMINIUM FINS
SOCKET TYPE	INTEL LGA 775/1366, AMD 754,930 & 940 AND AMD AM2/AM3
FAN SPECIFICATIONS	
DIMENSIONS (mm)	90 x 90 x 25 mm
WEIGHT	84.2g
FAN SPEED	900-2000 R.P.M. +-10% PWM
FAN AIRFLOW	19-37.98CFM
LIFE EXPECTANCY	MORE THAN 60000 hrs
BEARING	TACENS FLUXUS PRO BEARING
VOLTAGE RATING	10.2V-13.8V
NOISE LEVEL	9-19 dB

INTEL LGA775 /1366
AMD K8
(754, 939 & 940)
AMD AM2/AM3
MULTI- CORE
COMPATIBLE

NEW TACENS FLUXUS PRO BEARING

ULTRA SILENT

LOWER NOISE THAN SLEEVE OR BALL BEARINGS

DUST PROOF DESIGN

CLOSED CONSTRUCTION PREVENT THE DUST AND FOREIGN BODY INTO DE BEARING

LONG LIFE

MORE THAN 60000 hrs

LOW WORKING TEMPERATURE

THE FAN WORKS PERFECTLY IN VERY HOT CONDITIONS

ENVIRONMENTALY FRIENDLY

WWW.TACENS.COM **DESIGNED IN EUROPE**